


S71051 TEAK LIFE PROTETTIVO



Ready for use



1-2h at 20°C



By brush



By roller

Description

Protective impregnating oil for valuable woods. Suitable for the protection and preservation of different wood types that are used in the marine environment. It preserves wood for a long time thanks to its high penetration power into the fibres highlighting the wood's grain. It is recommended above all, for boat and yacht decks.

Colour

Straw-yellow

Characteristics

- High protective power

Substrate preparation

New wood

Clean and slightly sand with P 320 paper

Old wood

Carry out the treatment with the product line: Teak life detergente (detergent) and sbiancante (bleaching).

In summer it is recommended to repeat the treatment in the most worn out areas.

For further details on the product compatibility consult the relevant paint process technical data sheet.

Application

By brush or by roller.

Mixing ratio

Ready for use; if necessary dilute with thinner S70020 DILUENTE 277.

N° of coats: 1-2 (On old wood repeat the treatment as required, each coat 1-2 hours drying, until you get the desired aesthetical result).

Drying

	10°C	20°C	35°C
Sanding after	14 days	7 days	72 h
Overcoat after	min. 48 h max. 72 h	min. 24 h max. 36 h	min 12 h max. 18 h

TECHNICAL DATA SHEET N° S160-GB
UPDATED 03/2010

All information here included is the result of carefully controlled tests and expresses our best and up to date knowledge. This news is given only a guide, so the firm cannot be accountable for further results. Furthermore it cannot be used as a contestation related to the use of the described product. All this is due to the fact that use conditions are not under our control.